

ROADX

RXQUEST AT QX12



The RoadX RXQuest AT QX12 is the perfect all-terrain (A/T) tire for light truck, SUV and crossover drivers. The advanced tread pattern and aggressive sidewall allow it to handle all you can throw at it both on-and-off road terrains. This A/T tire is built to last while also providing a smooth and quiet ride for cruising. The wide shoulders provide excellent grip in wet conditions and the rim protector allows you to take on any trail with confidence in knowing that your wheels have that extra level of protection against the elements.

FEATURES

- Optimized contact patch for maximum traction and stability.
- Aggressive shoulder design increasing off-road bite and providing extra protection.
- Tread block edge is step style designed, reducing stone retention and road noise
- 3PMSF certified
- 50,000 Mile Limited Treadwear Warranty
- * Does not apply to Lt designated tires

Los vehículos de entrega de última milla están en todas partes, con entregas continuas tanto a negocios como a ubicaciones residenciales. Estos vehículos usualmente resisten múltiples paros, arranques y giros como parte de su día regular. El RoadX RXQUEST C11 está diseñado para soportar estas demandas diarias y asegura un neumático durable y confiable. Fabricado con un propósito, se incorporó un protector de pared lateral para asegurar la longevidad para cada flota grande o pequeña. Como los vehículos en los que están, el RXQUEST 11 hará el trabajo.

CARACTERÍSTICAS

- Sección de contacto optimizada para maximizar la tracción y la estabilidad.
- Diseño de hombro agresivo que incrementa el agarre fuera de la carretera y proporciona protección adicional.
- El borde del bloque de la banda de rodamiento está diseñado con estilo escalonado, reduciendo la retención de piedras y el ruido del camino.
- Certificado 3PMSF
- Garantía limitada de 50,000 millas en desgaste de la banda de rodadura
- * No aplica a neumáticos designados LT

ALL-TERRAIN TIRE

NEUMÁTICO TODOTERRENO

WET

DRY

COMFORT

QUIETNESS

TREAD LIFE



R, S, T SPEED RATED
600 A B UTQG



*P-METRIC & LT TIRES

ROADXTIRE.COM

ROADX

RXQUEST AT QX12

ALL-TERRAIN TIRE

NEUMÁTICO TODOTERRENO

PART NUMBER	SIZE	LI/SR	TD 32/IN.	OD IN.	SW IN.	RW IN.	UTQG	SINGLE MAX LOAD LBS@PSI	DUAL MAX LOAD LBS@PSI
1600092K	235/75R15	109S	13	28.9	9.3	6.5	600 A B		
1600088K	235/70R16	106S	13	29.0	9.5	7.0	600 A B		
1600095K	245/75R16	111S	13	30.5	9.8	7.0	600 A B		
1600099K	265/70R16	112T	13	30.6	10.7	8.0	600 A B		
1600101K	265/75R16	116S	13	31.7	10.5	7.5	600 A B		
1600087K	235/65R17	104S	13	29.1	9.5	7.0	600 A B		
1600093K	245/65R17	107S	13	29.5	9.8	7.0	600 A B		
1600094K	245/70R17	110T	13	30.6	9.8	7.0	600 A B		
1600097K	265/65R17	112S	13	30.6	10.7	8.0	600 A B		
1600100K	265/70R17	115S	13	31.7	10.7	8.0	600 A B		
1600098K	265/65R18	114T	13	31.5	10.7	8.0	600 A B		
1600090K	275/65R18	116T	13	32.1	11.0	8.0	600 A B		
1600096K	265/50R20	111T	13	30.5	10.9	8.5	600 A B		
1600121K	275/55R20	117T	13	31.9	11.2	8.5	600 A B		
1600089K	275/60R20	115T	13	33.0	11.0	8.0	600 A B		
1600091K	31X10.50R15LT	109S	16	30.5	10.6	8.5		2270@50	-
1600104K	LT235/75R15	104/101R	16	28.9	9.3	6.5		1985@50	1820@50
1600103K	LT225/75R16	115/112S	16	29.3	8.8	6.0		2680@80	2470@80
1600106K	LT235/85R16	120/116S	16	31.7	9.3	6.5		3042@80	2778@80
1600108K	LT245/75R16	120/116S	16	30.5	9.8	7.0		3042@80	2778@80
1600113K	LT265/75R16	123/120S	16	31.7	10.5	7.5		3415@80	3085@80
1600119K	LT285/75R16	126/123S	16	33.1	11.3	8.0		3750@80	3415@80
1600105K	LT235/80R17	120/117R	16	31.8	9.3	6.5		3085@80	2835@80
1600107K	LT245/70R17	119/116S	16	30.6	9.8	7.0		3000@80	2755@80
1600109K	LT245/75R17	121/118S	16	31.5	9.8	7.0		3195@80	2910@80
1600111K	LT265/70R17	121/118S	16	31.7	10.7	8.0		3195@80	2910@80
1600118K	LT285/70R17	121/118S	16	32.8	11.5	8.5		3195@80	2910@80
1600112K	LT265/70R18	124/121R	16	32.6	10.7	8.0		3525@80	3195@80
1600116K	LT275/65R18	123/120S	16	32.1	11.0	8.0		3415@80	3085@80
1600117K	LT275/70R18	125/122SR	16	33.2	11.0	8.0		3640@80	3305@80
1600110K	LT265/60R20	121/118R	16	32.5	10.7	8.0		3195@80	2910@80
1600114K	LT275/55R20	115/112S	16	31.9	11.2	8.5		2680@65	2470@65
1600115K	LT275/60R20	123/120R	16	33.0	11.0	8.0		3415@80	3085@80
1600102K	LT275/65R20	126/123S	16	34.1	11.0	8.0		3750@80	3415@80
1600120K	LT305/55R20	121/118R	16	33.2	12.4	9.5		3195@65	2910@65