

ROADX

RXQUEST AT QX12



PREMIUM ALL TERRAIN

The RXQuest AT QX12 is the perfect all-terrain (A/T) tire for light truck, SUV and crossover drivers. The advanced tread pattern and aggressive sidewall allow it to handle all you can throw at it both on-and-off road terrains. This A/T tire is built to last while also providing a smooth and quiet ride for cruising. The wide shoulders provide excellent grip in wet conditions and the rim protector allows you to take on any trail with confidence in knowing that your wheels have that extra level of protection against the elements.

FEATURES & BENEFITS

CONTROL

Optimized contact patch for maximum traction and stability.

TRUSTED GRIP

Aggressive shoulder design increasing off-road bite and providing extra protection.

BALANCED TRACTION

Tread block edge is step style designed, reducing stone retention and road noise

El RXQuest AT QX12 es el neumático todoterreno (A/T) perfecto para conductores de camionetas ligeras, vehículos utilitarios deportivos (SUV) y crossover. El patrón avanzado de la banda de rodamiento y la pared lateral agresiva le permiten manejar todo lo que pueda lanzarle en terrenos tanto dentro como fuera del camino. Este neumático A/T está fabricado para durar, además de ofrecer una conducción suave y silenciosa para crucero. Los hombros amplios proporcionan un agarre excelente en condiciones húmedas y el protector del aro le permite tomar cualquier camino con la confianza de saber que sus ruedas tendrán el nivel de protección adicional contra los elementos.

CARACTERÍSTICAS Y BENEFICIOS

CONTROL

Sección de contacto optimizada para maximizar la tracción y la estabilidad.

AGARRE CONFIABLE

Diseño de hombro agresivo que incrementa el agarre fuera de la carretera y proporciona protección adicional.

TRACCIÓN BALANCEADA

El borde del bloque de la banda de rodamiento está diseñado con estilo escalonado, reduciendo la retención de piedras y el ruido del camino.

PERFORMANCE RATINGS:



R, S, T SPEED RATED
600 A B UTQG



ROADXTIREUSA.COM

ROADX**RXQUEST AT QX12** 

PART NUMBER	SIZE	PR	LI/SR	TD 32/IN.	OD IN.	SW IN.	RW IN.	UTQG	SINGLE MAX LOAD LBS@PSI	DUAL MAX LOAD LBS@PSI
1600092K	235/75R15		109S XL	13	28.9	9.3	6.5	600 A B	2271@50	
1600088K	235/70R16		106S	13	29	9.5	7	600 A B	2094@44	
1600095K	245/75R16		111S	13	30.5	9.8	7	600 A B	2403@44	
1600099K	265/70R16		112T	13	30.6	10.7	8	600 A B	2469@44	
1600101K	265/75R16		116S	13	31.7	10.5	7.5	600 A B	2756@44	
1602169K	225/60R17		99T XL	13	27.6	9	6.5	600 A B	1709@44	
1602170K	225/65R17		106T XL	13	28.5	9	6.5	600 A B	2094@50	
1600087K	235/65R17		104S	13	29.1	9.5	7	600 A B	1984@44	
1600093K	245/65R17		107S	13	29.5	9.8	7	600 A B	2149@44	
1600094K	245/70R17		110T	13	30.6	9.8	7	600 A B	2337@44	
1600097K	265/65R17		112S	13	30.6	10.7	8	600 A B	2469@44	
1600100K	265/70R17		115S	13	31.7	10.7	8	600 A B	2679@44	
1602171K	235/60R18		107T XL	13	29.1	9.5	7	600 A B	2149@50	
1600098K	265/65R18		114T	13	31.5	10.7	8	600 A B	2601@44	
1600090K	275/65R18		116T	13	32.1	11	8	600 A B	2756@44	
1600096K	265/50R20		111T XL	13	30.5	10.9	8.5	600 A B	2403@50	
1600121K	275/55R20		117T XL	13	31.9	11.2	8.5	600 A B	2833@50	
1600089K	275/60R20		115T	13	33	11	8	600 A B	2679@44	
1602172K	275/50R22		115T XL	13	32.8	11.1	8.5	600 A B	2679@50	
1602126K	285/45R22		114H XL	13	32.1	11.2	9.5	600 A B	2601@50	
1600104K	LT235/75R15	6PR	104/101R	16	28.9	9.3	6.5		1985@50	1820@50
1600103K	LT225/75R16	10PR	115/112S	16	29.3	8.8	6		2680@80	2470@80
1600106K	LT235/85R16	10PR	120/116S	16	31.7	9.3	6.5		3042@80	2778@80
1600108K	LT245/75R16	10PR	120/116S	16	30.5	9.8	7		3042@80	2778@80
1600113K	LT265/75R16	10PR	123/120S	16	31.7	10.5	7.5		3415@80	3085@80
1600119K	LT285/75R16	10PR	126/123S	16	33.1	11.3	8		3750@80	3415@80
1600105K	LT235/80R17	10PR	120/117R	16	31.8	9.3	6.5		3085@80	2835@80
1600107K	LT245/70R17	10PR	119/116S	16	30.6	9.8	7		3000@80	2755@80
1600109K	LT245/75R17	10PR	121/118S	16	31.5	9.8	7		3195@80	2910@80
1600111K	LT265/70R17	10PR	121/118S	16	31.7	10.7	8		3195@80	2910@80
1600118K	LT285/70R17	10PR	121/118S	16	32.8	11.5	8.5		3195@80	2910@80
1600112K	LT265/70R18	10PR	124/121R	16	32.6	10.7	8		3525@80	3195@80
1600116K	LT275/65R18	10PR	123/120S	16	32.1	11	8		3415@80	3085@80
1600117K	LT275/70R18	10PR	125/122SR	16	33.2	11	8		3640@80	3305@80
1600110K	LT265/60R20	10PR	121/118R	16	32.5	10.7	8		3195@80	2910@80
1600114K	LT275/55R20	10PR	115/112S	16	31.9	11.2	8.5		2680@65	2470@65
1600115K	LT275/60R20	10PR	123/120R	16	33	11	8		3415@80	3085@80
1600102K	LT275/65R20	10PR	126/123S	16	34.1	11	8		3750@80	3415@80
1600120K	LT305/55R20	10PR	121/118R	16	33.2	12.4	9.5		3195@65	2910@65
1602173K	LT315/70R17	10PR	126/123S	16	34.4	12.7	9.5		3750@65	3415@65
1600091K	31X10.50R15LT	10PR	109S	16	30.5	10.6	8.5		2270@50	
1602174K	33X12.50R20LT	10PR	114S	16	33	12.5	10		2600@65	
1602127K	35X12.50R20LT	10PR	121R	16	35	12.5	10		3195@65	